

TRACK MAINTENANCE CARTS



TRACK MAINTENANCE CARTS


A **DymaxRail Track Maintenance Cart** is the perfect solution for moving equipment and materials in railway track construction and maintenance applications. Dymax Track Maintenance carts feature dual beam construction with steel plate decking and tie down locations. Options include slip on gondola bins, specialty hoppers, container locks, manual brakes, hydraulic or air brakes, train car couplers, towbars and DymaxRail's solar powered automatic directional change lighting and travel alarm systems. Dymax Rail Carts can be towed behind hi-rail machinery such as grapple trucks or railcar movers but also work with DymaxRail's Rail Rider MPX.

Contact DymaxRail sales for more information on **Rail Track Maintenance Carts**.

**CUSTOM DESIGN
SOLUTIONS**

**SOLAR POWERED
LIGHTING SYSTEMS**

**SPECIALIZED BRAKING
SOLUTIONS**



DYMEXRAIL | Toll Free: 800.530.5407 (USA/CAN)
402 Miller Drive | Office: +1.785.456.2081
Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMEXRAIL.com
sales@DYMEXRAIL.com

RAILWAY TRACK MAINTENANCE CARTS STANDARD GAUGE 1435MM

| Uniform Load Capacity rating | 15 ton | 30 ton | 45 ton |
|------------------------------|--|--|--|
| Sizes (width x length) | 8ft x 12ft 8ft x 16ft 8ft x 20ft | 8ft x 12ft 8ft x 16ft 8ft x 20ft | 8ft x 12ft 8ft x 16ft 8ft x 20ft |
| Wheel / Axle Group | 16" x 3.00 in axles | 16" x 3.50 in axles | 16" x 4.00 in axles |
| Decking | Steel plate | | |
| Standard | Tie down locations and lifting points | | |
| Brake | Select Brake kit below | | |

UPGRADES TO BASIC CART SYSTEMS

| | | | |
|--|--|--------------------|------------|
| Light Kit AD | Auto-directional system; Red and White lights (2) each on each side of trailer. System features standard sensor system and includes Spot lamp on each side of trailer. | | |
| Light Package B | Relay flash lighting package; Red and White lights (2) each on both trailer ends. Sytem features integrated battery system, solar panel chargers and protectors. Lights flash alternating pattern continuously. Features switch bulkhead for turning on and off. | | |
| Alarm Kit | Grote Alarm system with decibal measuring ability - setup on switch bank with lights | | |
| Air Brake 2 wheels + manual park brake | Non-Locking Pod System,- brakes set with air supplied; Setup with glad hands on both trailer ends and parking brake on opposing side. | | |
| Air Brake 4 wheels | Locking pod system, air to release design - brakes set always without air supplied; Setup with glad hands on both trailer ends | | |
| Park Brake - Screw type | Manual screw adjuster with friction pad shoe. | | |
| Tow bar | 4ft 8ft 12ft | 4ft 8ft 12ft | 4ft 8ft |
| Tie Upright Stakes | 8 or 12 tie stakes provided with retainers - 6 feet height | | |
| Slip on Gondola Box 2 bin | 30" wall height designed with HD tube frame. Slips on main cart group to create box cart | | |
| Side Dump Gondola Box with open side | Call for details; System features it's own intermediate frame that will attach to Dymax base cart but features additional hydraulic requirements depending on machinery available. | | |

Design and Specifications subject to change without notice.



DYMAXRAIL | Toll Free: 800.530.5407 (USA/CAN)
 402 Miller Drive | Office: +1.785.456.2081
 Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXRAIL.com
sales@DYMAXRAIL.com