

JCB 110WRX RAIL EXCAVATOR



KNOW NO BOUNDARIES

JCB 110WRX RAIL EXCAVATOR

In a world where space and track time is limited and infrastructure demands are at an all time high, the **JCB 110WRX** by **DymaxRail** delivers the most power and performance of any machine in its class. Engineered to be different from the rails up the Hydradig 110WRX railway excavator features a specialized chassis including innovative Rail Rider hi-rail systems and significantly lower center of gravity to greatly improve stability when working overside. A space capsule like cabin gives operators full perspective with endless views of their surroundings. See more and do more with a JCB 110WRX railway excavator by DymaxRail.

FEATURES

- **25 MILES PER HOUR** WITH 3 CONFIGURABLE SETTINGS INCLUDING WORKSITE AND CREEP MODES
- **50% MORE** LIFT CAPACITY OVERSIDE WITH RAIL RIDER HI-RAIL SYSTEMS
- **LESS TAIL SWING** FOR ADJACENT LINE WORK
- **SPACE CAPSULE CABIN** GIVES OPERATORS BEST IN CLASS VISIBILITY WITH NO OBSTRUCTIONS BEHIND THEM.
- **TRIPLE ARTICULATING SWING BOOM** DELIVERS POWER, PERFORMANCE AND BETTER APPLICATION REACH ANGLES FOR TUNNELS, CATENARY SYSTEMS AND CITY TRANSITS OR TERMINAL RAILWAYS.
- **4 HYDRAULIC CIRCUITS** INCLUDING A HYDRAULIC HANDHELD TOOL CIRCUIT
- **DYMEXRAIL ATTACHMENTS** AND TILTROTATOR SYSTEMS
- **FULLY INTEGRATED SYSTEM DESIGN** AVAILABLE FOR RAILROADS, CONTRACTORS AND TRANSITS INCLUDING 3RD RAIL APPLICATIONS



JCB 110WRX RAIL EXCAVATOR

SPECIFICATIONS

Model Code/Description	Features
DX-WHX-HY-JCBHDIG-HX-11T	Wheel Excavator-Hydraulic-JCB Hydradig-Hydraulic Excavator-11 Ton
<p>JCB 110W T4F TAB Triple Articulating Boom 2.0m 315/70R-22 spaceless dual heavy wall tires • High flow hydraulic lines with case drain line • 2x medium pressure, low flow lines • Handheld tool circuit (one side) • Trailer towing kit with clevis • Road Kit • Tool Kit • Cold Climate Kit • Dymax Rail Rider Hi-Rail systems include front and rear rail systems, spring suspension, hydraulic stabilizers, fail safe brakes, in cab remote and warning systems, auto steer shutoff, directional lighting systems, installation package Operating weight (machine only): 28,900 lbs</p>	
Select Package Below and Attachments	
Quick Coupler Solutions	
<ul style="list-style-type: none"> Hydraulic pin grab coupler system - compatible with 3cx and 4cx backhoes Tiltrotator coupler systems available upon request 	
Buckets and Thumbs	
<ul style="list-style-type: none"> 12", 14", 18", 24", 30", 36", 42" Hydraulic thumb 	
Specialized Railway Buckets	
<ul style="list-style-type: none"> 8" cribbing bucket 10" crib-clam bucket with 360° rotation 42" tilt bucket 36" clamshell bucket 360° Ditching bucket 	
Ballast Maintenance Specialized Work Tool Attachments	
<ul style="list-style-type: none"> Ballast Blaster Undercutter BB8 8ft cut length x 360° rotation Ballast Tamper - DymaxRail - Single Motor with rotation Ballast Tamper - DymaxRail - Twin Workhead Ballast Tamper - DymaxRail - Twin Motor 6700 style workhead with rotation 	
Railtie and Misc Specialized Work Tool Attachments	
<ul style="list-style-type: none"> Wood Tie Handler with optional rake or whale fin blade Concrete Tie Handler with optional rake or whale fin blade Tie Extractor and Inserter attachment for changing wood ties Rail Handler for handling up to 40ft rail pieces and insulated joints Magnet with Generator 10" Limb Shear or HPX forestry tree shear Mulcher - cuts up to 8" materials Rotary Style 48" Brushcutter - cuts up to 6" material Rail tool carts TieShear Attachment 	
<p>Design and specifications are subject to change without notice. Options are available depending on your requirements. Contact DymaxRail for more information. 2/2020 Specialized attachment design solutions available</p>	



DYMAXRAIL | Toll Free: 800.530.5407 (USA/CAN)
 402 Miller Drive | Office: +1.785.456.2081
 Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXRAIL.com
sales@DYMAXRAIL.com