

TRANSFORMING RAILWAY MAINTENANCE

EXCAVATOR TRANSFER SHUTTLE





EXCAVATOR TRANSFER SHUTTLE

Move large excavators to remote worksites with the DymaxRail Excavator Transfer Shuttle. It's powered by an engine cart and remote control system, without any machine modifications. Excavators can crawl off the track and get to work quickly.

KEY FEATURES & BENEFITS:

- Standalone Transport Solution: The shuttle is operated through a remote control and compact hydraulic power unit. No machine modifications.
- Hydraulic Drive System: Smooth, controlled movement along railway tracks.
- Integrated Stabilizers: Safe and stable transport.











WIRELESS CONTROLS

CAMERA

HAND TOOLS



402 Miller Drive

DYMAXRAIL | Toll Free: 800.530.5407 (USA/CAN)

Office: +1.785.456.2081 Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXRAIL.com sales@DYMAXRAIL.com





	4
Model No.	Weight (lbs/kg)
Group No. Description	
DX-TRSL-EXEL-118x28ft-DMX-36T	28,500 / 12,927
6085D2: Shuttle Transporter-Excavator End-Load-118 inches wide x 28 feet length + includes Power	
Cart-DymaxRail-36 Ton	
POWER CAR FEATURES	
Engine: 275HP power system with hydrostatic pump	
Hydraulic hand tool circuit with hose reel and flow control	
• Side step and handle bars • Mechanical brake with cobra friction shoe	
Directional lighting with LED spot lamps	
Amber beacon strobe • Acetalyne tank holders	
• Toolbox and storage bin • Bulkhead disconnects (hydraulic and electrical)	
• Train horn • Power car size: 127x80 inches less muffler	
Air compressor for air brakes	
EXCAVATOR CART FEATURES	
• 118 inches wide (142" with swingouts) x 28 feet cart length • Height off rail: 27 inches	
• Twin hydraulic drive axles • 4-point hydraulic stabilizers	
Heavy duty ramps • Apitong wood decking	
• Red & white directional lighting control system with LED spot lamps	
Boom stow bucket rest • Adjustable grouser stops	
• Side outriggers with boards provided to make overall width 142 inches on rail	
Remote control supplied with foot pedal for in-cab operation	
Rear bolster group with twin axles; front single axle	
Hydraulic release, spring set brakes with external disconnects	
• Thru-pass air lines for attaching to air brake trailers with gladhand connections	
• Tie down locations and lift locations	
Towbar for power car included with stow location	
• Pin eye hitches	

Design and specifications are subject to change without notice. Contact DymaxRail for more information.



Includes remote camera solution for enhanced visibility on the rear of the power car.

DYMAXRAIL | Toll Free: 800.530.5407 (USA/CAN)

402 Miller Drive | Office: +1.785.456.2081 Wamego, KS 66547 USA | Fax: +1.785.456.8328

www.DYMAXRAIL.com sales@DYMAXRAIL.com