

EXCAVATOR TRANSFER SHUTTLE



EXCAVATOR TRANSFER SHUTTLE

Move large excavators to remote worksites with the DymaxRail **Excavator Transfer Shuttle**. It's powered by an engine cart and remote control system, without any machine modifications. Excavators can crawl off the track and get to work quickly.

KEY FEATURES & BENEFITS:

- **Standalone Transport Solution:** The shuttle is operated through a remote control and compact hydraulic power unit. No machine modifications.
- **Hydraulic Drive System:** Smooth, controlled movement along railway tracks.
- **Integrated Stabilizers:** Safe and stable transport.



WIRELESS CONTROLS



CAMERA



HAND TOOLS



Model No.	Weight (lbs/kg)
Group No. Description	
<p>DX-TRSL-EXEL-118x28ft-DMX-36T 6085D2: Shuttle Transporter-Excavator End-Load-118 inches wide x 28 feet length + includes Power Cart-DymaxRail-36 Ton</p> <p>POWER CAR FEATURES</p> <ul style="list-style-type: none"> • Engine: 275HP power system with hydrostatic pump • Hydraulic hand tool circuit with hose reel and flow control • Side step and handle bars • Mechanical brake with cobra friction shoe • Directional lighting with LED spot lamps • Amber beacon strobe • Acetalene tank holders • Toolbox and storage bin • Bulkhead disconnects (hydraulic and electrical) • Train horn • Power car size: 127x80 inches less muffler • Air compressor for air brakes <p>EXCAVATOR CART FEATURES</p> <ul style="list-style-type: none"> • 118 inches wide (142" with swingouts) x 28 feet cart length • Height off rail: 27 inches • Twin hydraulic drive axles • 4-point hydraulic stabilizers • Heavy duty ramps • Apitong wood decking • Red & white directional lighting control system with LED spot lamps • Boom stow bucket rest • Adjustable grouser stops • Side outriggers with boards provided to make overall width 142 inches on rail • Remote control supplied with foot pedal for in-cab operation • Rear bolster group with twin axles; front single axle • Hydraulic release, spring set brakes with external disconnects • Thru-pass air lines for attaching to air brake trailers with gladhand connections • Tie down locations and lift locations • Towbar for power car included with stow location • Pin eye hitches <p>Includes remote camera solution for enhanced visibility on the rear of the power car.</p>	28,500 / 12,927

Design and specifications are subject to change without notice. Contact DymaxRail for more information.



DYMAXRAIL
402 Miller Drive
Wamego, KS 66547 USA

Toll Free: 800.530.5407 (USA/CAN)
Office: +1.785.456.2081
Fax: +1.785.456.8328

www.DYMAXRAIL.com
sales@DYMAXRAIL.com