

**HYDRAULIC CLAM CRIBBING BUCKET**

ONE BUCKET. MULTIPLE RAIL JOBS.

Fits: Backhoe + Hydraulic Excavators
Rotation: 360 degree rotation or made to fit tiltrotator
Hydraulics: Requires 1 auxiliary circuit with two-way valve

The **DymaxRail Hydraulic Clam Cribbing Bucket** simplifies ballast track maintenance like no other. Whether you're cribbing between ties or pulling and replacing them, this high-performance attachment delivers up to 2.5x the productivity of traditional attachments, especially when working from hi-railed positions.

In the right conditions, operators can efficiently replace up to 250 ties per day, making it one of the most effective solutions for rail maintenance crews.

APPLICATIONS

- Crib ballast directly from hi-rail positions.
- Insert and change railroad ties with speed and control.
- Move and reposition rail pieces up to 39 feet.
- Ideal for track rehabilitation & maintenance.
- Trusted by class 1 railroads, shortlines, contractors and transit agencies.

KEY BENEFITS

- Perform multiple jobs with one attachment. Crib ballast, pull and insert ties, move rails and handle materials.
- Reduce attachment changes to boost overall efficiency.
- Built with AR400 steel for long-lasting durability in harsh ballast environments.
- Powerful digging, with 20 tons of force per bucket.



CRIB BALLAST

MOVE RAIL

CHANGE TIES

MODEL CODE	DESCRIPTION	WEIGHT (LBS)	HYDRAULIC REQUIREMENTS
Models with 360 rotation systems for fitting pin or wedge type coupler systems			
DX-BK-CLAM-10inx360-BL-10	Bucket-Clam-10 inches wide x 360 degrees rotation-Backhoe Loader-Class 10	1150	Your machine will require the following (1x) circuits to operate the attachment. This attachment is supplied with an electro-hydraulic valve and provided with cable harness and switch kit.
DX-BK-CLAM-10inx360-HX-8T	Bucket-Clam-10 inches wide x 360 degrees rotation-Hydraulic Excavator-8 Ton	1150	
DX-BK-CLAM-10inx360-HX-12T	Bucket-Clam-10 inches wide x 360 degrees rotation-Hydraulic Excavator-12 Ton	1400	CIRCUIT 1 - CLAM OPEN / CLOSE Type: Two-way bi-directional flow GPM/PSI: 10-20 @ 3,000 psi max CIRCUIT 2 - ROTATION Type: Electro-hydraulic Includes cable harness and switch kit. NOT SUPPLIED: Jumper hose lines from attachment bulkhead to machine.
DX-BK-CLAM-10inx360-HX-20T	Bucket-Clam-10 inches wide x 360 degrees rotation-Hydraulic Excavator-20 Ton	2100	
Models for fitting tiltrotator coupler systems			
DX-BK-CLAM-10inxTRQ-BL-10	Bucket-Clam-10 inches wide x Tiltrotator coupler hookup-Backhoe Loader-Class 10	740	Your machine will require the following (1x) circuits to operate the attachment.
DX-BK-CLAM-10inxTRQ-HX-8T	Bucket-Clam-10 inches wide x Tiltrotator coupler hookup-Hydraulic Excavator-8 Ton	740	
DX-BK-CLAM-10inxTRQ-HX-12T	Bucket-Clam-10 inches wide x Tiltrotator coupler hookup-Hydraulic Excavator-12 Ton	740	CIRCUIT 1 - CLAM OPEN / CLOSE Type: Two-way bi-directional flow GPM/PSI: 15-20 @ 3,000 psi max NOT SUPPLIED: Jumper hose lines from attachment bulkhead to machine.
DX-BK-CLAM-10inxTRQ-HX-20T	Bucket-Clam-10 inches wide x Tiltrotator coupler hookup-Hydraulic Excavator-20 Ton	740	
For 360 rotating models only: If your machine is equipped with 2 auxiliary circuits and you do not require the electro-valve, please contact DymaxRail Sales.			
Design and specifications are subject to change without notice.			



DYMAXRAIL
 402 Miller Drive
 Wamego, KS 66547 USA
 Toll Free: 800.530.5407 (USA/CAN)
 Office: +1.785.456.2081
 Fax: +1.785.456.8328

www.DYMAXRAIL.com
sales@DYMAXRAIL.com